

Primary Deck Covering Solutions

	Product	Estimated Consumption per m ²	Pumpable	Recommended Thickness	Compressive Strength	Area Of Usage
Self-Levelling	weberfloor 4660N Marine Elastic	1,7 kg/mm	Yes	5 – 40 mm	33 N/mm ²	Suitable for all areas including wet areas and heavy traffic areas
	weberfloor 4680N Marine Light	0,9 kg/mm	Yes	10 – 30 mm	21 N/mm ²	Public areas with heavy foot traffic and medium traffic
	weberfloor 4686N Marine Extra Light	0,65 kg/mm	Yes	10 – 30 mm	12 N/mm ²	Passengers areas with light foot traffic such as cabins and offices
Mortar	weberfloor 4670N Marine Base	1,8 kg/mm	No	20 – 150 mm	35 N/mm ²	Wet areas and thicker layers for slopes building
	weberfloor 4769N Epoxy Mortar	2,0 kg/mm	No	3 – 100 mm	70 N/mm ²	Indoors, outdoors, and wet areas with thinner layers. Suitable for skirtings
Multi-purpose	weberfloor 4690N Marine Combi	1,6 kg/mm	No	1 – 50 mm	34 N/mm ²	Repair works, repairing cracks, repairing cement underlayment
Thicker Layers	weberfloor 4660N Marine Elastic + LWA	0,9 kg/mm	No	10 – 100 mm	33 N/mm ²	Weight-saving solution for thicker layers
	weberfloor 450 Light	0,65 kg/mm	Yes	30 – 600 mm	12-33 N/mm ²	Weight-saving solution for thicker layers